



2021 Enduro Rules and Procedures

Saturday, September 18, 2021

Ladies – 4 cylinders

Mens – 4 cylinders

Trucks

Sunday, September 19, 2021

Mens – 6 cylinders

Mens – 8 cylinders

Mens – Vans

Mens – Open Class (all remaining cars together)

NOTE - If less than 16 cars ($\frac{1}{2}$ the laps & $\frac{1}{2}$ the purse) per class

**IF CMS SPEEDWAY -TECH APPROVED ROLL CAGE IS USED, DOUBLE THE PURSE
MONEY-UP TO \$250**

\$50 per registered car

**THE CORNWALL MOTOR SPEEDWAY INC, ALL OF OUR SPEEDWAY SPONSORS, OFFICIALS AND
MANAGEMENT ARE NOT RESPONSIBLE FOR DEATH OR INJURIES THAT MAY OCCUR ON THIS DAY. YOU
TAKE FULL RESPONSIBILITY OF YOUR WELL BEING WHEN ENTERING THIS COMPETITION.**

No Alcohol or drugs permitted in the pit area

Pit opens at 8am, Drivers and Scorers meeting are scheduled at 1pm, racing will start at 2pm

**Scorers must attend the meeting 1pm or their car will not be scored, the meeting will be held in the
grandstands near the flagstand.**

Purses are:

Mens 4 cylinders: 1. \$300; 2. \$200; 3. \$100

Mens 6 cylinders: 1. \$300; 2. \$200; 3. \$100

Mens 8 cylinders: 1. \$500; 2. \$300; 3. \$100


Mens Vans: 1. \$300; 2. \$200; 3. \$100

Ladies 4 cylinders: \$300; 2. \$200; 3. \$100

Mens Trucks: 1.\$300; 2. \$200; 3.\$100


The following applies to Ladies 4 cylinders and Mens 4 cylinders

NOTE: Leave front doors blank for number on Race Day.

<ol style="list-style-type: none"> 1. Any 4-cylinder car 2. <i>All glass and flammable materials</i> must be removed. 3. No outside reinforcement allowed. 4. Maximum 6" tires (tread width). 5. No cutting or gutting of any panels. 6. No bracing in front of front firewall. 7. No trucks, 4-wheel drives or convertibles. 8. Car must have full body. 9. No obscene lettering. 10. Tire pressure, no less than 28 lbs. per tire. 11. No holes in floor @ drivers feet. 12. No plastic body cars. ie: Saturns 13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets 	<p style="text-align: center;"><u>SAFETY</u></p> <ol style="list-style-type: none"> 1. <input type="checkbox"/> Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver 2. <input type="checkbox"/> Lap & shoulder belt. 3. <input type="checkbox"/> Full face helmet. 4. <input type="checkbox"/> Seat must be solid to floor or roll cage. 5. <input type="checkbox"/> Gas tank in original position. If not, it must be in trunk strapped with at least 4, 1" strapping. Firewall between driver compartment and trunk. 6. <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Trunk has to be bolted and NOT Welded 7. <input type="checkbox"/> ALL DOORS MUST BE WELDED SHUT. At least 4, 1" welds per door.  8. <input type="checkbox"/> 4 point roll bar highly recommended. 9. <input type="checkbox"/> Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE. 10. <input type="checkbox"/> Remove all air bags. 11. <input type="checkbox"/> <input type="checkbox"/> No Mounting of anything on the roof of the vehicle 12. <input type="checkbox"/> <input type="checkbox"/> NECK RESTRAINTS Highly recommended

The following applies to Mens 6 cylinders

NOTE: Leave front doors blank for number on Race Day.


<ol style="list-style-type: none"> 1. Any 6-cylinder car 2. <i>All glass and flammable materials</i> must be removed. 3. No outside reinforcement allowed. 4. Maximum 6" tires (tread width). 5. No cutting or gutting of any panels. 6. No bracing in front of front firewall. 7. No trucks, 4-wheel drives or convertibles. 8. Car must have full body. 9. No obscene lettering. 10. Tire pressure, no less than 28 lbs. per tire. 11. No holes in floor @ drivers feet. 12. No plastic body cars. ie: Saturns 13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets 	<p style="text-align: center;"><u>SAFETY</u></p> <ol style="list-style-type: none"> 1. <input type="checkbox"/> Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver 2. <input type="checkbox"/> Lap & shoulder belt. 3. <input type="checkbox"/> Full face helmet. 4. <input type="checkbox"/> Seat must be solid to floor or roll cage. 5. <input type="checkbox"/> Gas tank in original position. If not, it must be in trunk strapped with <u>at least 4</u>, 1" strapping. Firewall between driver compartment and trunk. 6. <input type="checkbox"/><input type="checkbox"/><input type="checkbox"/> Trunk has to be bolted and NOT Welded 7. <input type="checkbox"/> ALL DOORS MUST BE WELDED SHUT. At least 4, 1" welds per door.  8. <input type="checkbox"/> 4 point roll bar highly recommended. 9. <input type="checkbox"/> Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE. 10. <input type="checkbox"/> Remove all air bags. 11. <input type="checkbox"/><input type="checkbox"/> No Mounting of anything on the roof of the vehicle 12. <input type="checkbox"/><input type="checkbox"/> NECK RESTRAINTS Highly recommended
--	--

The following applies to Mens 8 cylinders

NOTE: Leave front doors blank for number on Race Day.


1. Any North American Car. NO 4-cylinders compact car
2. *All glass and flammable materials* must be removed.
3. **No** outside reinforcement allowed.
4. Maximum 6" tires (tread width).
5. **No** cutting or gutting of any panels.
6. **No** bracing in front of front firewall.
7. **No** trucks, 4-wheel drives or convertibles.
8. Car must have full body.
9. **No** obscene lettering.
10. Tire pressure, no less than 28 lbs. per tire.
11. **No** holes in floor @ drivers feet.
12. **No** plastic body cars. ie: Saturns
13. SUNROOF must be closed with TIN
14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets

SAFETY

1. ☐ Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver
2. ☐ Lap & shoulder belt.
3. ☐ Full face helmet.
4. ☐ Seat must be solid to floor or roll cage.
5. ☐ Gas tank in original position. If not, it must be in trunk strapped with **at least 4**, 1" strapping.
Firewall between driver compartment and trunk.
6. ☐☐☐ Trunk has to be bolted and NOT Welded
7. ☐ ALL DOORS **MUST BE WELDED SHUT**. At least **4**,
1" welds per door. 
8. ☐ 4 point roll bar highly recommended.
9. ☐ Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE.
10. ☐ Remove all air bags.
11. ☐☐ No Mounting of anything on the roof of the vehicle
12. ☐☐ NECK RESTRAINTS Highly recommended

The following applies to Mini-Van

NOTE: Leave front doors blank for number on Race Day.


<ol style="list-style-type: none"> 1. Any 4 OR 6 cylinder Mini-Van 2. <i>All glass and flammable materials</i> must be removed. 3. No outside reinforcement allowed. 4. Maximum 6" tires (tread width). 5. No cutting or gutting of any panels. 6. No bracing in front of front firewall. 7. No trucks, 4-wheel drives or convertibles. 8. Car must have full body. 9. No obscene lettering. 10. Tire pressure, no less than 28 lbs. per tire. 11. No holes in floor @ drivers feet. 12. No plastic body cars. ie: Saturns 13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets 	<p style="text-align: center;"><u>SAFETY</u></p> <ol style="list-style-type: none"> 1. <input type="checkbox"/> Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver 2. <input type="checkbox"/> Lap & shoulder belt. 3. <input type="checkbox"/> Full face helmet. 4. <input type="checkbox"/> Seat must be solid to floor or roll cage. 5. <input type="checkbox"/> Gas tank in original position. If not, it must be in trunk strapped with at least 4, 1" strapping. Firewall between driver compartment and trunk. 6. <input type="checkbox"/><input type="checkbox"/><input type="checkbox"/> Trunk has to be bolted and NOT Welded 7. <input type="checkbox"/> ALL DOORS MUST BE WELDED SHUT. At least 4, 1" welds per door.  8. <input type="checkbox"/> 4 point roll bar highly recommended. 9. <input type="checkbox"/> Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE. 10. <input type="checkbox"/> Remove all air bags. 11. <input type="checkbox"/><input type="checkbox"/> No Mounting of anything on the roof of the vehicle 12. <input type="checkbox"/><input type="checkbox"/> NECK RESTRAINTS Highly recommended
--	---

The following applies to Trucks

NOTE: Leave front doors blank for number on Race Day.

1. Any North American Truck 8 Cyl
2. *All glass and flammable materials* must be removed.
3. **No** outside reinforcement allowed.
4. Maximum 9" tires (tread width).
5. **No** cutting or gutting of any panels.
6. **No** bracing in front of front firewall.
7. **No** 4-wheel drives (must be disconnected).
8. Truck must have full stock body.
9. **No** obscene lettering.
10. Tire pressure, no less than 36 lbs. per tire.
11. **No** holes in floor @ drivers feets.
12. **No** plastic body cars.
13. SUNROOF must be closed with TIN
14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets

SAFETY

1. ☐ Battery must be in original place.
2. ☐ Lap & shoulder belt.
3. ☐ Full face helmet.
4. ☐ Seat must be solid to floor or roll cage.
5. ☐ Gas tank in original position.
6. ☐☐☐ Trunk has to be bolted and NOT Welded
7. ☐ ALL DOORS **MUST** BE WELDED SHUT. At least 4,
1" welds per door. 
8. ☐ 4 point roll bar highly recommended.
9. ☐ Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE.
10. ☐ Remove all air bags.
11. ☐☐ No Mounting of anything on the roof of the vehicle
12. ☐☐ NECK RESTRAINTS Highly recommended