



2022 Enduro Rules and Procedures

Saturday, September 10, 2022

Ladies – 4 cylinders

Mens-4 cylinders

Trucks

Sunday, September 11, 2022

Mens-6 cylinders

Mens-8 cylinders

Mens-Vans

Mens-Open Class (all remaining cars together)

NOTE - If less than 16 cars (1/2 the laps & 1/2 the purse) per class

IF CMS SPEEDWAY -TECH APPROVED ROLL CAGE IS USED, DOUBLE THE PURSE MONEY-UP TO \$250

\$50 per registered car

THE CORNWALL MOTOR SPEEDWAY INC, ALL OF OUR SPEEDWAY SPONSORS, OFFICIALS AND MANAGEMENT ARE NOT RESPONSIBLE FOR DEATH OR INJURIES THAT MAY OCCUR ON THIS DAY. YOU TAKE FULL RESPONSIBILITY OF YOUR WELL BEING WHEN ENTERING THIS COMPETITION.

No Alcohol or drugs permitted in the pit area

Pit opens at 8am, Drivers and Scorers meeting are scheduled at 1pm, racing will start at 2pm

Scorers must attend the meeting 1pm or their car will not be scored, the meeting will be held in the grandstands near the flag stand.

Purses are:

Mens 4 cylinders: 1. \$300; 2. \$200; 3. \$100

Mens 6 cylinders: 1. \$300; 2. \$200; 3. \$100

Mens 8 cylinders: 1. \$500; 2. \$300; 3. \$100

Mens Vans: 1. \$300; 2. \$200; 3. \$100

Ladies 4 cylinders: \$300; 2. \$200; 3. \$100

Mens Trucks: 1.\$300; 2. \$200; 3.\$100

The following applies to Ladies 4 cylinders and Mens 4 cylinders

NOTE: Leave front doors blank for number on Race Day.		
1. Any 4-cylinder car	<u>SAFETY</u>	
2. All glass and flammable materials must be removed.	1. Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
3. No outside reinforcement allowed.	2. Lap & shoulder belt.	
4. Maximum 6" tires (tread width).	3.□ Full face helmet.	
5. No cutting or gutting of any panels.	4. Seat must be solid to floor or roll cage.	
6. No bracing in front of front firewall.	5. Gas tank in original position. If not, it must be in trunk	
7. No trucks, 4-wheel drives or convertibles.	strapped with at least 4 , 1" strapping. Firewall between driver compartment and trunk.	
8. Car must have full body.	6. \Box \Box \Box Trunk has to be bolted and NOT Welded	
9. No obscene lettering.	7. ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
10. Tire pressure, no less than 28 lbs. per tire.	1" welds per doorX X X X	
11. No holes in floor @ drivers feets.	8 🛛 4 point roll bar highly recommended.	
 12. No plastic body cars. ie: Saturns 13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets 	 9. □ Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE. 	
	10. Remove all air bags.	
	11. O No Mounting of anything on the roof of the vehicle	
	12. Image: NECK RESTRAINTS Highly recommended I. Image: Strange Stra	
	, , ,	

The following applies to Mens 6 cylinders

NOTE: Leave front doors blank for number on Race Day.		
1. Any 6-cylinder car	<u>SAFETY</u>	
2. All glass and flammable materials must be removed.	1. Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
3. No outside reinforcement allowed.		
4. Maximum 6" tires (tread width).	2. Lap & shoulder belt.	
5. No cutting or gutting of any panels.	3. Full face helmet.	
6. No bracing in front of front firewall.	4. Seat must be solid to floor or roll cage.	
7. No trucks, 4-wheel drives or convertibles.	5.□ Gas tank in original position. If not, it must be in trunk strapped with <u>at least</u> 4, 1" strapping.	
8. Car must have full body.	Firewall between driver compartment and trunk.	
9. No obscene lettering.	6. \Box \Box \Box Trunk has to be bolted and NOT Welded	
10. Tire pressure, no less than 28 lbs.	7. D ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
per tire. 11. No holes in floor @ drivers feets.	1" welds per doorX X X X	
12. No plastic body cars. ie: Saturns 13. SUNROOF must be closed with TIN	8 🛛 4 point roll bar highly recommended.	
13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets	9. Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE.	
	10. 🗆 Remove all air bags.	
	11. O No Mounting of anything on the roof of the vehicle	
	13. Gloves are mandatory.	

NOTE: Leave front doors blank for number on Race Day.		
1. Any North American Car. NO 4- cylinders compact car	SAFETY	
2. All glass and flammable materials must be removed.	1. Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
3. No outside reinforcement allowed.	2.□ Lap & shoulder belt.	
4. Maximum 6" tires (tread width).	3. Full face helmet.	
5. No cutting or gutting of any panels.	4.□ Seat must be solid to floor or roll cage.	
6. No bracing in front of front firewall.	5. Gas tank in original position. If not, it must be in trunk	
7. No trucks, 4-wheel drives or convertibles.	strapped with at least_4 , 1" strapping.	
8. Car must have full body.	Firewall between driver compartment and trunk.	
9. No obscene lettering.	6. \Box \Box \Box $Trunk$ has to be bolted and NOT Welded	
	7. ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
10. Tire pressure, no less than 28 lbs. per tire.	1" welds per doorX X	
11. No holes in floor @ drivers feets.	X X	
12. No plastic body cars. ie: Saturns	8 🛛 4 point roll bar highly recommended.	
13. SUNROOF must be closed with TIN	9. Windshield area must be completely covered with	
14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides,	wire screen no larger than 2" holes. NO CHICKEN WIRE.	
screwed from inside or rivets	10. Remove all air bags.	
	11. O No Mounting of anything on the roof of the vehicle	
	12. Image: NECK RESTRAINTS Highly recommended13. Image: Gloves are mandatory.	

The following applies to Mens 8 cylinders

NOTE. Leave front	doors blank for number on Race Day.	
1. Any 4 OR 6 cylinder Mini-Van	<u>SAFETY</u>	
2. All glass and flammable materials must be removed.	1. Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
3. No outside reinforcement allowed.	2. Lap & shoulder belt.	
4. Maximum 6" tires (tread width).	3.□ Full face helmet.	
5. No cutting or gutting of any panels.	4. \Box Seat must be solid to floor or roll cage.	
 No bracing in front of front firewall. No trucks 4 wheel drives or 	5. Gas tank in original position. If not, it must be in trunk strapped with <u>at least</u> 4, 1" strapping.	
7. No trucks, 4-wheel drives or convertibles.	Firewall between driver compartment and trunk.	
8. Car must have full body.	6. \Box \Box \Box Trunk has to be bolted and NOT Welded	
9. No obscene lettering.	7. ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
10. Tire pressure, no less than 28 lbs. per tire.	1" welds per doorX X X X	
11. No holes in floor @ drivers feets.	8 🛛 4 point roll bar highly recommended.	
 12. No plastic body cars. ie: Saturns 13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, 	 9. Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE. 	
screwed from inside or rivets	10. 🗆 Remove all air bags.	
	11. \Box \Box No Mounting of anything on the roof of the vehicle	
	12.	
	13. Gloves are mandatory.	

The following applies to Mini-Van

The following applies to Trucks		
NOTE: Leave front doors blank for number on Race Day.		
1. Any North American Truck 6 or 8	<u>SAFETY</u>	
Cyl	1. Battery must be in original place.	
2. All glass and flammable materials must	2. Lap & shoulder belt.	
be removed.	3.□ Full face helmet.	
3. No outside reinforcement allowed.	4. Seat must be solid to floor or roll cage.	
4. Maximum 9" tires (tread width).	5. \Box Gas tank in original position.	
5. No cutting or gutting of any panels.	6. \Box \Box \Box Trunk has to be bolted and NOT Welded	
6. No bracing in front of front firewall.	7. ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
7. No 4-wheel drives (must be disconnected).	1" welds per doorX X	
8. Truck must have full stock body.	8 a 4 point roll bar highly recommended.	
9. No obscene lettering.	 9. Windshield area must be completely covered with 	
10. Tire pressure, no less than 36 lbs. per tire.	wire screen no larger than 2" holes. NO CHICKEN WIRE.	
11. No holes in floor @ drivers feets.	10. 🗆 Remove all air bags.	
 12. No plastic body cars. 13. SUNROOF must be closed with TIN 14. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets 	 11. O No Mounting of anything on the roof of the vehicle 12. O NECK RESTRAINTS Highly recommended 13. O Gloves are mandatory. 	