



2024 Enduro Rules and Procedures

Saturday, September 7, 2024

Ladies – 4 cylinders

Mens - 4 cylinders

Mens - 6 cylinders

Open (All remaining Saturday cars)

Sunday, September 8, 2024

Mens - 8 cylinders

Mens - Vans

Mens - Trucks

Trailer Race

Mens – Open Class (all remaining cars together)

NOTE - If less than 16 cars (½ the laps & ½ the purse) per class

IF CMS SPEEDWAY -TECH APPROVED ROLL CAGE IS USED, DOUBLE THE PURSE MONEY-UP TO \$250

\$50 per registered car (Enduro) and \$20 for Trailer Race, Pole Race and Backward Race

THE CORNWALL MOTOR SPEEDWAY INC, ALL OF OUR SPEEDWAY SPONSORS, OFFICIALS AND MANAGEMENT ARE NOT RESPONSIBLE FOR DEATH OR INJURIES THAT MAY OCCUR ON THIS DAY. YOU TAKE FULL RESPONSIBILITY OF YOUR WELL BEING WHEN ENTERING THIS COMPETITION.

No Alcohol or drugs permitted in the pit area

Pit opens at 9am (10am on Sunday), Driver's meeting scheduled at 1pm and Scorers at 1:30pm, racing will start at 2pm

Scorers must attend the meeting 1:30pm or their car will not be scored, the meeting will be held in the grandstands near the flag stand.

Purses are:

Mens 4 cylinders: 1. \$300; 2. \$200; 3. \$100

Mens 6 cylinders: 1. \$300; 2. \$200; 3. \$100

Mens 8 cylinders: 1. \$500; 2. \$300; 3. \$100

Mens Vans: 1. \$300; 2. \$200; 3. \$100

Ladies 4 cylinders: \$300; 2. \$200; 3. \$100

Mens Trucks: 1. \$300; 2. \$200; 3. \$100

Trailer Race: Purse to be determined on number of cars registered.

TRAILER RACE RULES

Open to any driver and any Enduro Car, Mini Van, Small SUV, Jeep or Small Pick Up and is a 15-lap race. To be declared the winner your trailer must still be attached to your car on the 15th lap when you cross the line. If you lose your trailer prior to the end of the race you are allowed to continue racing and try to remove your competitors trailer.

Rules for the Trailer are as follows:

- No pintle type hitches or no homemade style hitches, must be a standard ball and coupler type hitch.
- Ball may be attached to the trailer in any manor however cannot stick out past the rear bumper more than a standard ball would.
- No semi-trailers, or semi-trailer axles or tires.
- If your trailer includes a boat or anything of that nature fuel and fluids must be drained from the boat.
- We encourage boats, furniture, or any other original trailer ideas.

PLUS bonus for most original trailer (voted by fans):

1st place: pair of pit tickets for Canadian Super DIRT Weekend (Sunday) - \$100 2nd place: pair of pit tickets for Canadian Super DIRT Weekend (Saturday) - \$90 3rd place: pair of pit tickets for Canadian Super DIRT Weekend (Friday) - \$80

The following applies to Ladies 4 cylinders and Mens 4 cylinders

NOTE: Leave front doors blank for number on Race Day.		
Any 4-cylinder car	<u>SAFETY</u>	
All glass and flammable materials must be removed.	1. Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
must be removed. 3. No outside reinforcement allowed. 4. No cutting or gutting of any panels. 5. No bracing in front of front firewall. 6. No trucks, 4-wheel drives or convertibles. 7. Car must have full body. 8. Front and rear plastic bumpers must be removed. All Styrofoam packing 9. Trailer hitch allowed (original place) 10. Remove all working lights, no mirror 11. Tires allowed are the ones that come with the model of car (Winter tires are allowed) 12. Tire pressure, no less than 28 lbs. per tire. 13. No obscene lettering.	relocated if needed, must solid to floor and secured from the driver 2. Lap & shoulder belt. 3. Full face helmet. 4. Seat must be solid to floor or roll cage. 5. Gas tank in original position. If not, it must be in trunk strapped with at least. 4, 1" strapping. Firewall between driver compartment and trunk. 6. Trunk has to be bolted and NOT Welded 7. ALL DOORS MUST BE WELDED SHUT. At least 4, 1" welds per door. X X X X 8 4 point roll bar highly recommended. 9. Windshield area must be completely covered with wire screen no larger than 2" holes. NO CHICKEN WIRE. 10. Remove all air bags.	
14. 11. No holes in floor @ drivers feets.	11. □□ No Mounting of anything on the roof of the vehicle 12. □□ NECK RESTRAINTS Highly recommended 13. □ Gloves are mandatory	
15. No plastic body cars. ie: Saturns16. SUNROOF must be closed with TIN17. On the roof a piece of thin TIN 1 x 1f foot with your Number on both sides, screwed from inside or rivets	13. □ Gloves are mandatory.	

The following applies to Mens 6 cylinders

NOTE: Leave front doors blank for number on Race Day.		
1. Any 6-cylinder car	<u>SAFETY</u>	
All glass and flammable materials must be removed.	1. ☐ Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from	
3. No outside reinforcement allowed.	the driver	
4. No cutting or gutting of any panels.	2.□ Lap & shoulder belt.	
5. No bracing in front of front firewall.	3. □ Full face helmet.	
6. No trucks, 4-wheel drives or	4.□ Seat must be solid to floor or roll cage.	
convertibles. 7. Car must have full body.	5. ☐ Gas tank in original position. If not, it must be in trunk strapped with at least_4 , 1" strapping.	
·	Firewall between driver compartment and trunk.	
8. Front and rear plastic bumpers must be removed. All Styrofoam packing must be removed	6. □ Trunk has to be bolted and NOT Welded	
	7. □ ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
Trailer hitch allowed (original place)	1" welds per door. X X	
10. Remove all working lights, no mirror	X X	
11. Tires allowed are the ones that come with the model of car (Winter tires are allowed)	8 4 point roll bar highly recommended.	
	9. Windshield area must be completely covered with	
12. Tire pressure, no less than 28 lbs. per tire.	wire screen no larger than 2" holes. NO CHICKEN WIRE.	
13. No obscene lettering.	10. Remove all air bags.	
14. 11. No holes in floor @ drivers feets.	 11. □□ No Mounting of anything on the roof of the vehicle 12. □□ NECK RESTRAINTS Highly recommended 13. □ Gloves are mandatory. 	
15. No plastic body cars. ie: Saturns 16. SUNROOF must be closed with TIN 17. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets		

The following applies to Mens 8 cylinders

NOTE: Leave front doors blank for number on Race Day.		
1. Any North American Car. NO 4-	<u>SAFETY</u>	
cylinders compact car2. All glass and flammable materials must be removed.	1.☐ Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
3. No outside reinforcement allowed.	2.□ Lap & shoulder belt.	
4. No cutting or gutting of any panels.	3.□ Full face helmet.	
5. No bracing in front of front firewall.	4. ☐ Seat must be solid to floor or roll cage.	
6. No trucks, 4-wheel drives or convertibles.	5.□ Gas tank in original position. If not, it must be in trunk strapped with at least 4 , 1" strapping.	
7. Car must have full body.	Firewall between driver compartment and trunk.	
8. Front and rear plastic bumpers must be removed. All Styrofoam packing must be removed	6. □ Trunk has to be bolted and NOT Welded	
	7. ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
9. Trailer hitch allowed (original place)	1" welds per door. X X	
10. Remove all working lights, no mirror	X X	
11. Tires allowed are the ones that	8 \(\text{4 point roll bar highly recommended.} \)	
come with the model of car (Winter tires are allowed)	9. Windshield area must be completely covered with wire screen no larger than 2" holes. NO	
12. Tire pressure, no less than 28 lbs.	CHICKEN WIRE.	
per tire.	10. ☐ Remove all air bags.	
13. No obscene lettering.	11.□□ No Mounting of anything on the roof of the vehicle	
14. No holes in floor @ drivers feets.	12. □□ NECK RESTRAINTS Highly recommended13. □ Gloves are mandatory.	
15. No plastic body cars. ie: Saturns		
16. SUNROOF must be closed with TIN		
17. On the roof a piece of thin TIN 1 x 1		
f foot with your Number on both sides, screwed from inside or rivets		

The following applies to Mini-Van

NOTE: Leave front doors blank for number on Race Day.		
1. Any 4 OR 6 cylinder Mini-Van	<u>SAFETY</u>	
All glass and flammable materials must be removed	1. ☐ 1. ☐ Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from	
3. No outside reinforcement allowed.	the driver	
4. Tires allowed are the ones that come with the model of car (Winter tires	2. Lap & shoulder belt.3. Full face helmet.	
are allowed)	4. ☐ Seat must be solid to floor or roll cage.	
5. No cutting or gutting of any panels.6. Front and rear plastic bumpers must	5. ☐ Gas tank in original position. If not, it must be in trunk strapped with <u>at least</u> 4, 1" strapping.	
be removed. All Styrofoam packing must be removed	Firewall between driver compartment and trunk.	
7. No bracing in front of front firewall.	6. ☐ Trunk has to be bolted and NOT Welded	
8. Trailer hitch allowed (original place)	7. □ ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
9. Remove all working lights, no mirror	1" welds per door. X X	
10. No trucks, 4-wheel drives or	X X	
convertibles.	8 \(\text{4 point roll bar highly recommended.} \)	
11. Van must have full body.	9. Windshield area must be completely covered with	
12. No obscene lettering.	wire screen no larger than 2" holes. NO CHICKEN WIRE.	
13. Tire pressure, no less than 28 lbs. per tire.	10. ☐ Remove all air bags.	
14. No holes in floor @ drivers feets.	11.□□ No Mounting of anything on the roof of the vehicle12.□□ NECK RESTRAINTS Highly recommended	
15. No plastic body cars. ie: Saturns 16. SUNROOF must be closed with TIN 17. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets	13. □ Gloves are mandatory.	

The following applies to Trucks

NOTE: Leave front doors blank for number on Race Day.		
1. Any North American Truck 6 or 8	<u>SAFETY</u>	
All glass and flammable materials must be removed	1. ☐ Battery must be in engine compartment. It can be relocated if needed, must solid to floor and secured from the driver	
3. No outside reinforcement allowed.	2. □ Lap & shoulder belt.	
4. Maximum 10" tires (tread width).	3. ☐ Full face helmet.	
(Winter Tires are allowed)	4. ☐ Seat must be solid to floor or roll cage.	
5. No cutting or gutting of any panels.	5. ☐ Gas tank in original position. If not, it must be in trunk	
6. No bracing in front of front firewall.	strapped with <u>at least</u> 4, 1" strapping.	
7. No 4-wheel drives (must be	Firewall between driver compartment and trunk.	
disconnected).	6. ☐ Trunk has to be bolted and NOT Welded	
8. Truck must have full stock body.	7. ALL DOORS MUST BE WELDED SHUT. At least 4 ,	
9. Trailer hitch allowed (original place)	1" welds per door. ──X X	
10. Remove all working lights, no mirror	1" welds per door. X X	
11. No obscene lettering.	8 \(\text{4 point roll bar highly recommended.} \)	
12. Tire pressure, no less than 36 lbs. per tire.	9. ☐ Windshield area must be completely covered with wire screen no larger than 2" holes. NO	
13. No holes in floor @ drivers feets.	CHICKEN WIRE.	
 14. No plastic body cars. 15. SUNROOF must be closed with TIN 16. On the roof a piece of thin TIN 1 x 1 f foot with your Number on both sides, screwed from inside or rivets 	 10. □ Remove all air bags. 11. □ No Mounting of anything on the roof of the vehicle 12. □ NECK RESTRAINTS Highly recommended 13. □ Gloves are mandatory. 	